



Cooper ECOPACK Generator Series

Diesel | CNG | LPG



10kVA to 750kVA

World Class Generators now Made in India

TECHNICAL SPECIFICATIONS

ENGINE MODEL	GENERATOR OUTPUT KVA	GENERATOR OUTPUT KWe	ENGINE OUTPUT KwM	BHP	NUMBER OF CYLINDERS	ASPIRATION	GOVERNOR	ENGINE DISPLACEMENT (liters)	RATED CURRENT (Amps)	IN-BUILT FUEL TANK CAPACITY (liters)	ACOUSTIC ENCLOSURE DIMENSIONS L (mm) x W (mm) x H (mm)	APPROX. WEIGHT (kgs.)
AL 40T G3	50	40	56.2	76.4	4	TC	Mechanical	4.01	70	250	3100 x 1200 x 1580	1532
AL 40T G3	62.5	50	56.2	76.4	4	TC	Mechanical	4.01	88	250	3100 x 1200 x 1580	2056
AL 40T1 G2	75	60	76	103.2	4	TCA	Mechanical	4.01	115	250	3100 x 1200 x 1580	2165
AL 40T1 G2	82.5	66	76	103.2	4	TCA	Mechanical	4.01	115	250	3100 x 1200 x 1580	2165
AL 60T1 G1	100	80	89.8	122	6	TCA	Electronic	5.76	139	250	4000 x 1250 x 1752	2308
AL 60T1 G2	125	100	112.5	152.8	6	TCA	Electronic	5.76	174	250	4000 x 1250 x 1752	2457
AL 680TA G2	140	112	131.7	179	6	TCA	Mechanical	11.10	195	400	4300 x 1500 x 1983	3585
AL 680TA G3	160	128	150	203.8	6	TCA	Mechanical	11.10	222	400	4300 x 1500 x 1983	3585
AL 615TA G2	180	144	165.7	225.2	6	TCA	Electronic	9.73	250	400	4700 x 1600 x 2050	3800
AL 615TA G1	200	160	185.5	252	6	TCA	Electronic	9.73	278	400	4700 x 1600 x 2050	4000
ALGW0618.42D	250	200	228.2	310	6	TCA	Electronic	11.50	348	400	4700 x 1600 x 2050	4305
P126T1	275	220	241.4	328	6	TCA	Electronic	11.05	383	580	5500 x 2080 x 2395	5250
P126T1	320	256	284.1	386	6	TCA	Electronic	11.05	445	580	5500 x 2080 x 2395	5500
P158LE	400	320	363.6	494	8	TCA	Electronic	14.62	556	850	5500 x 2080 x 2395	6000
P 180LE	500	400	443.1	602	10	TCA	Electronic	18.27	695	850	5500 x 2080 x 2395	6500
P 222LE	600	480	532.1	723	12	TCA	Electronic	21.93	834	850	6260 x 2080 x 2580	7000
Z206C-E13TAG3	400	320	368	493	6	TCA	Electronic	21.50	556	893	5600 x 1850 x 2255	5400
Z506C-E15TAG2	500	400	451	605	6	TCA	Electronic	15.20	695	893	5600 x 1850 x 2260	5700
Z806C-E18TAG1A	600	480	532	713	6	TCA	Electronic	18.10	834	990	5600 x 1850 x 2410	6300
4006-23TAG2A	750	600	658	882	6	TCA	Electronic	22.92	1043	External Fuel Tank	7500 x 2500 x 2500	8000

ED112/10

OPTIONAL: • Single phase ratings from 10 KVA to 40 KVA • Heat Exchanger cooled DG Sets • AMF / Synchronising Panels / MCC • Mobile / Trolley Mounted Deisel Generator Sets
 NOTES: • Standard gensets are available in Radiator cooling. • Alternators: Self excited with Class F insulation, IP23 protection, 1500 rpm, 50Hz, 3 phase, 0.8 pf, 415V • Alternator make Trident / Leroy Somer / equivalent (at supplier's option) • As a process of continual improvement, above data is subject to change



Registered Office & Works :
 L-3 , Addl. M.I.D.C. , Post Kodoli,
 Satara - 415001. Maharashtra (INDIA)
 Telephone: +91 - 2162 - 240413, 240272
 Fax: +91 - 2162 - 240271, 240023
 Email: contact@coopercorp.in
www.coopergenset.com

Central Marketing Office :
 Unit#1, Trident, S.No. 13/3/4,
 NDA-Pashan Road, Bavdhan,
 Pune - 411 021. Maharashtra (INDIA)
 Telephone : +91 - 20 - 22952696
 Fax : +91 - 20 - 22952696
 Email: powergen@coopercorp.in

Authorised Dealer